

BarFly® 450 DMX & 200D



The BarFly® 450 DMX & 200D are the next generation of this BarFly lighting systems. The soft cool beauty lights feature a narrow profile of 4.5" in depth with onboard dimming ballasts, lamp switching and universal input voltage (100VAC-240VAC). The BarFly 450 also features DMX dimming and DMX lamp switching.

The BarFly 450 is brighter than a 1,000 Watt tungsten softlight, but draws only 2 amps, while the BarFly 200D is equivalent to a 500 Watt tungsten softlight drawing only 1 amp of power. Both fixtures include a built-in reflector and removable gel frame, honeycomb louver and center mount. The lightweight fixtures are ideal for difficult tight shots on location or in the studio. The fixtures take 3200K and 5500K True Match® lamps that display a full range of high color rendering (CRI 95) soft light.

Features include:

- Narrow profile
- Flicker-free, dead quiet
- Onboard and remote dimming
- Individual lamp switching
- DMX dimming and DMX lamp switching (BarFly 450)
- Universal input 100VAC-240VAC
- Removable Center Mount
- Reflector, Louver and Gel Frame
- True Match® daylight and tungsten balanced lamps

▼ BarFly 450 DMX Kit



KIT-B450-120U
BarFly 450 DMX Kit, Univ 120U (1-Unit)

KIT-B450-230U
BarFly 450 DMX Kit, Univ 230U (1-Unit)

Contents	Dimensions
1 BarFly 450 DMX	31.5 x 9 x 22"
1 Mount	(80 x 23 x 56cm)
1 Medium Duty Stand, 30"	
1 Lamp Case	Weight
1 Travel Case	32 lb (14.5kg)

▼ BarFly 200D Kits



KIT-B22D-120U
BarFly 200D Kit, Univ 120U (2-Unit)

KIT-B22D-230U
BarFly 200D Kit, Univ 230U (2-Unit)

Contents	Dimensions
2 BarFly 200D	31.5 x 9 x 22"
2 Mount	(80 x 23 x 56cm)
2 Reverse Stand	Weight
1 Lamp Case	39.5 lb (18kg)
1 Travel Case	



KIT-B200D-120U
BarFly 200D Kit, Univ 120U (1-Unit) w/ Soft Case

KIT-B200D-230U
BarFly 200D Kit, Univ 230U (1-Unit) w/ Soft Case

Contents	Dimensions
1 BarFly 200D	20.5 x 10 x 14"
1 Mount	(52 x 25.5 x 36cm)
1 Soft Case	Weight
	15 lb (7kg)

▼ Photometrics

BarFly 450	FC	631	166	76	43	28	20	15	11	9	7
	Feet	2	4	6	8	10	12	14	16	18	20
BarFly 200D	FC	298	80	36	20	13	9	7	5	4	3.5
	Feet	2	4	6	8	10	12	14	16	18	20
BarFly 450	LUX	9150	2659	1206	689	445	310	230	180	142	116
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5
BarFly 200D	LUX	4662	1260	571	324	211	147	110	85	68	55
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

▼ Fixture Specifications

Fixture	Input Voltage	Output Frequency	Amperage	Dimming Range	Lamp Switching	Lamps	Dimensions	Weight w/Lamps
BarFly 450	100-240VAC	47kHz	2.4A, 120V 1.2A, 230V	100-5%	1-4	4 x 55W QFL	17 x 16 x 4.5" (43 x 41 x 11.5cm)	12 lb (5.5kg)
BarFly 200D	100-240VAC	47kHz	1.2A, 120V 0.7A, 230V	100-5%	1-2	2 x 55W QFL	16 x 9.5 x 4.5" (41 x 24 x 11.5cm)	7.5 lb (3.5kg)

▼ Details



▼ BarFly 450 DMX System



▼ BarFly 200D System



Bill Brennan



Fernando Escovar



David Mann

▼ BarFly Accessories/ Lamps

