

Celeb® 400 DMX LED



The Celeb® 400 DMX joins Kino Flo's line of LED lighting systems. With soft, even True Match® light quality (CRI 95), the Celeb 400 boasts technical innovations that make it an ideal professional imaging tool: dial-in white light from 2700 to 5500 Kelvin and presets with programmable settings. Light levels do not change when selecting Kelvin settings. The Celeb also includes full range dimming without color shift.

The Celeb 400 DMX operates at universal input from 100VAC-240VAC or battery power. The slim profile fixture produces more lumens than a 1K tungsten softlight, yet uses only 1.8A (120VAC) compared to a tungsten softlight at 8.3A. The Celeb comes with molded accessory holders, removable gel frame and focusing louver.

Features include:

- Kelvin presets and custom settings between 2700-5500K
- Universal input 100VAC-240VAC or 24VDC
- Onboard and DMX dimming
- Flicker-free, dead quiet operation
- Gel Frame and Honeycomb Louver
- Center Mount, Yoke Mount and Pole-Op

▼ Celeb 400 DMX LED Center




CEL-400C-120U
Celeb 400 DMX
Center Mount, Univ 120U

CEL-400C-230U
Celeb 400 DMX
Center Mount, Univ 230U



GFR-CE4
Celeb 400 Gel Frame
(Included)



LVR-CE490
Celeb 400 Louver 90°
(Included)



MTP-LM
Kino 81 Lollipop w/
Junior Pin (28mm)
(Included)

▼ Celeb 400 DMX LED Yoke



CEL-400Y-120U
Celeb 400 DMX
Yoke Mount, Univ 120U

CEL-400Y-230U
Celeb 400 DMX
Yoke Mount, Univ 230U




CEL-400P-120U
Celeb 400 DMX
Pole-Op, Univ 120U

CEL-400P-230U
Celeb 400 DMX
Pole-Op, Univ 230U



GFR-CE4
Celeb 400 Gel Frame
(Included)



LVR-CE490
Celeb 400 Louver 90°
(Included)

▼ Photometrics

	FC	687	220	105	61	40	28	21	16	13	11
	Feet	2	4	6	8	10	12	14	16	18	20
Celeb 400	LUX	9800	3423	1647	958	634	442	331	258	208	168
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

▼ Fixture Specifications

Fixture	Input Voltage VAC	Amps VAC	Input Voltage VDC	Amps VDC	Kelvin Range	Dimming Range	Dimensions	Weight
Celeb 400 DMX Center	100-240VAC, 50/60Hz, 210W	1.8A	18-28VDC, 198W	8.25A	2700-5500	100%-1%	45 x 14 x 5" (114.5 x 36 x 13cm)	26 lb (12kg)
Celeb 400 DMX Center	240-100VAC, 50/60Hz, 207W	1.0A	18-28VDC, 198W	8.25A	2700-5500	100%-1%	45 x 14 x 5" (114.5 x 36 x 13cm)	26 lb (12kg)
Celeb 400 DMX Yoke	100-240VAC, 50/60Hz, 210W	1.8A	18-28VDC, 198W	8.25A	2700-5500	100%-1%	50 x 16.5 x 5" (127 x 42 x 13cm)	26 lb (12kg)
Celeb 400 DMX Yoke	240-100VAC, 50/60Hz, 207W	1.0A	18-28VDC, 198W	8.25A	2700-5500	100%-1%	50 x 16.5 x 5" (127 x 42 x 13cm)	26 lb (12kg)

▼ Details



Bill Roe



Bill Roe



Bill Roe

▼ Celeb 400 DMX LED Kits



KIT-C4-120U
Celeb 400 DMX Center Mount Kit, Univ 120U



KIT-C4Y-120U
Celeb 400 DMX Yoke Mount Kit, Univ 120U

KIT-C4-230U
Celeb 400 DMX Center Mount Kit, Univ 230U

KIT-C4Y-230U
Celeb 400 DMX Yoke Mount Kit, Univ 230U

Contents
1 Celeb 400 DMX Center
1 Ship Case

Dimensions
51 x 9.5 x 19"
(129.5 x 24 x 48.5cm)

Weight
48 lb (22kg)

Contents
1 Celeb 400 DMX Yoke
1 Jr. Pin
1 Ship Case

Dimensions
53.5 x 9 x 23.5"
(136 x 23 x 60cm)

Weight
53 lb (24kg)

▼ Celeb 400 DMX LED Accessories/ Cases



BRD-CE4
Celeb 400 Barndoors
(Set of 4)



LVR-CE460
Celeb 400 Louver 60°



MTP-180
Junior Pin Assembly
for Yoke (28mm)



7010045
Celeb 400
Yoke Assembly



7010046
Celeb 400
Pole-Op Assembly



KAS-CE4
Celeb 400 Center Ship Case

KAS-CE4-Y
Celeb 400 Yoke Ship Case