

BarFly® 400D & 200D



The BarFly® 400D & 200D are the next generation of thin BarFly lighting systems. The soft, cool beauty lights feature a narrow profile of 4.5" in depth with onboard dimming ballasts, lamp switching and Universal input voltage (100VAC-240VAC). The BarFly 400D is brighter than a 1,000 Watt tungsten softlight, but draws only 2 amps, while the BarFly 200D is brighter than a 500 Watt tungsten softlight drawing only 1 amp of power. The new BarFly's include a built-in reflector and removable gel frame, honeycomb louver and center mount. The lightweight fixtures are ideal for difficult tight shots on location or in the studio. The fixtures take 3200K and 5500K True Match® lamps that display a full range of high color rendering (CRI 95) soft light.

Features include:

- Narrow profile
- Onboard dimming
- Remote dimming
- Individual lamp switching
- Flicker-free, dead quiet
- Universal Input 100VAC–240VAC
- Removable Center Mount
- Reflector, Louver and Gel Frame
- True Match® daylight and tungsten balanced lamps

▼ BarFly 400D Kit



KIT-B41D-120U
BarFly 400D Kit, 120U (1-Unit)

KIT-B41D-230U
BarFly 400D Kit, 230U (1-Unit)

Contents	Dimensions
1 BarFly 400D	31.5 x 9 x 22"
1 Mount	(80 x 22.9 x 56cm)
1 Medium Duty Stand	Weight
1 Lamp Case	30 lb (13.6kg)
1 Travel Case	

▼ BarFly 200D Kits



KIT-B22D-120U
BarFly 200D Kit, 120U (2-Unit)

KIT-B22D-230U
BarFly 200D Kit, 230U (2-Unit)

Contents	Dimensions
2 BarFly 200D	31.5 x 9 x 22"
2 Mount	(80 x 22.9 x 56cm)
2 Reverse Stand	Weight
1 Lamp Case	37 lb (16.8kg)
1 Travel Case	



KIT-B200D-120U
BarFly 200D Kit, 120U (1-Unit) w/ Soft Case

KIT-B200D-230U
BarFly 200D Kit, 230U (1-Unit) w/ Soft Case

Contents	Dimensions
1 BarFly 200D	20.5 x 9.5 x 13.5"
1 Mount	(52 x 24.1 x 34.3cm)
1 Soft Case	Weight
	15 lb (6.8kg)

▼ Photometrics

BarFly 400D	FC	534	148	68	38	25	17.5
	Feet	2	4	6	8	10	12

BarFly 200D	FC	344	96	43	25	16	11
	Feet	2	4	6	8	10	12

BarFly 400D	LUX	7967	2048	1066	614	395	274
	Meters	0.5	1	1.5	2	2.5	3

BarFly 200D	LUX	5297	1496	678	383	250	174
	Meters	0.5	1	1.5	2	2.5	3

▼ Fixture Specifications

Fixture	Input Voltage	Output Frequency	Dimming Range	Lamp Switch	Amps	Lamps	Dimensions	Weight w/Lamps
BarFly 400D	100-240VAC	47kHz	100-5%	1-4	2.4A, 120V 1.2A, 230V	4 x 55W OFL	17 x 16 x 4.5" (43 x 41 x 11.4cm)	12 lb (5.4kg)
BarFly 200D	100-240VAC	47kHz	100-5%	1-2	1.2A, 120V 0.7A, 230V	2 x 55W OFL	16 x 9.5 x 4.5" (41 x 24 x 11.4cm)	7.5 lb (3.4kg)

▼ Details



Billy Brennan



Fernando Escovar



David Mann

▼ BarFly Accessories/ Lamps

	BAR-400D-120U BarFly 400D, 120U		STD-D1 Reverse Stand
	BAR-400D-230U BarFly 400D, 230U		STD-M30 Medium Duty, 30"
	BAR-200D-120U BarFly 200D, 120U		KAS-B4-C BarFly 400D Travel Case (1-Unit)
	BAR-200D-230U BarFly 200D, 230U		KAS-B22-C BarFly 200D Travel Case (2-Unit)
	DIM-5 Remote Dimmer		BAG-B21 BarFly 200D Soft Case
	LVR-B460 BarFly 400 Louver 60°		KAS-QL6 6-Lamp Carry Case (Quad)
	LVR-B445 BarFly 400 Louver 45°		55Q-K32 55W Kino KF32 Quad
	LVR-B260 BarFly 200 Louver 60°		55Q-K55 55W Kino KF55 Quad
	LVR-B245 BarFly 200 Louver 45°		
	MTP-KL41 Kino 41L Mount w/ 3/8" Pin (10mm)		

▼ BarFly 400D System

	SYS-B400D-120U BarFly 400D System, 120U
	SYS-B400D-230U BarFly 400D System, 230U
	GFR-B4 BarFly 400 Gel Frame (Included)
	LVR-B490 BarFly 400 Louver 90° (Included)
	MTP-BL41 Kino 41L Mount w/ Baby Rcvr (16mm) (Included)

▼ BarFly 200D System

	SYS-B200D-120U BarFly 200D System, 120U
	SYS-B200D-230U BarFly 200D System, 230U
	GFR-B2 BarFly 200 Gel Frame (Included)
	LVR-B290 BarFly 200 Louver 90° (Included)
	MTP-BL41S Kino 41L Mount w/ Baby Rcvr Short (16mm) (Included)