


# Imara® DMX



Rope Hang



Pole-Operation

The Imara® S10 and S6 are studio fixtures with the characteristics of the Image series, but with a more concentrated spread of light along both horizontal and vertical axes. The Imara S10 puts out about the same light output as the VistaBeam 610, yet draws only 5.2A at 120VAC (2.6A at 230VAC). The all-in-one Imara DMX fixtures also feature new levels of control by combining lamp switching and lamp dimming, making them ideal for film production, TV broadcast and digital photography. Both models use Kino Flo's True Match® high color rendering 55W compact lamps (CRI 95) available in tungsten and daylight.

Key features are:

- DMX and manual lamp switching
- DMX and manual lamp dimming
- Reflector, Louver and Gel Frame
- True Match® daylight and tungsten balanced lamps

Available in Yoke Mount or Pole-Op.

## ▼ Imara S10 DMX



**IMR-S10-120**  
Imara S10 DMX Yoke,  
120VAC



**IMR-S10-P120**  
Imara S10 DMX Pole-Op,  
120VAC



**IMR-S10-230**  
Imara S10 DMX Yoke,  
230VAC



**IMR-S10-P230**  
Imara S10 DMX Pole-Op,  
230VAC



**GFR-IM10**  
Imara S10 Gel Frame  
(Included)



**GFR-IM10**  
Imara S10 Gel Frame  
(Included)



**LVR-IM1090**  
Imara S10 Louver 90°  
(Included)



**LVR-IM1090**  
Imara S10 Louver 90°  
(Included)

## ▼ Imara S6 DMX



**IMR-S6-120**  
Imara S6 DMX Yoke,  
120VAC



**IMR-S6-P120**  
Imara S6 DMX Pole-Op,  
120VAC



**IMR-S6-230**  
Imara S6 DMX Yoke,  
230VAC



**IMR-S6-P230**  
Imara S6 DMX Pole-Op,  
230VAC



**GFR-IM6**  
Imara S6 Gel Frame  
(Included)



**GFR-IM6**  
Imara S6 Gel Frame  
(Included)



**LVR-IM690**  
Imara S6 Louver 90°  
(Included)



**LVR-IM690**  
Imara S6 Louver 90°  
(Included)

▼ Photometrics

<b>Imara S10</b>	FC	580	280	165	108	77	57	44	35
	Feet	4	6	8	10	12	14	16	18
<b>Imara S6</b>	FC	338	158	92	59	44	31	24	19
	Feet	4	6	8	10	12	14	16	18

<b>Imara S10</b>	LUX	8720	4295	2562	1690	1206	904	689	560
	Meters	1	1.5	2	2.5	3	3.5	4	4.5
<b>Imara S6</b>	LUX	5211	2465	1432	937	687	490	378	300
	Meters	1	1.5	2	2.5	3	3.5	4	4.5

▼ Fixture Specifications

Fixture	Input Voltage	Output Frequency	Dimming Range	Lamp Switch	Amps	Lamps	Dimensions	Weight w/Lamps
<b>Imara S10 DMX</b>	120VAC 50/60Hz	30kHz	100-5%	2/4/6/8/10	5.2A	10 x 55W CFL	41 x 27 x 7" (104 x 68.5 x 18cm)	31 lb (14kg)
<b>Imara S10 DMX</b>	230VAC 50/60Hz	30kHz	100-5%	2/4/6/8/10	2.6A	10 x 55W CFL	41 x 27 x 7" (104 x 68.5 x 18cm)	31 lb (14kg)
<b>Imara S6 DMX</b>	120VAC 50/60Hz	30kHz	100-5%	2/4/6	3.2A	6 x 55W CFL	28 x 27 x 7" (71 x 68.5 x 18cm)	21 lb (9.5kg)
<b>Imara S6 DMX</b>	230VAC 50/60Hz	30kHz	100-5%	2/4/6	1.5A	6 x 55W CFL	28 x 27 x 7" (71 x 68.5 x 18cm)	21 lb (9.5kg)

▼ Details



▼ Imara Accessories/ Lamps

	<b>BRD-IM10</b> Imara S10 Bardoors		<b>KAS-IM10-1</b> Imara S10 Ship Case
	<b>BRD-IM6</b> Imara S6 Bardoors		<b>KAS-IM6-1</b> Imara S6 Ship Case
	<b>LVR-IM1060</b> Imara S10 Louver 60°		<b>55C-K32</b> 55W Kino KF32 Compact
	<b>LVR-IM660</b> Imara S6 Louver 60°		<b>55C-K55</b> 55W Kino KF55 Compact
	<b>MTP-180</b> Junior Pin Assembly for Yoke (28mm)		
	<b>KAS-CL6</b> 6-Lamp Carry Case (55W Compact)		

▼ Beam Spread



Imara S10 open face



Imara S10 w/ 90° louvers



Imara S10 w/ 60° louvers

The Imara utilizes a SoftCut reflector designed to emit a bright, narrow even spread of soft light. The edges of the beam are distinct. This concentration is useful in TV studios and photographic applications where the subject is localized and the spread of light is required to be more directed.

Compare the Imara S10 light beam characteristics open faced and using the 90° and 60° honeycomb louvers.

▼ Imara S10 DMX Kit



**KIT-IM10-1/120**  
Imara S10 DMX Yoke Mount Kit, 120VAC

**KIT-IM10-1/230**  
Imara S10 DMX Yoke Mount Kit, 230VAC

<b>Contents</b>	<b>Dimensions</b>
1 Imara S10 DMX Yoke	44.5 x 10.5 x 35.5"
1 Jr. Pin	(113 x 27 x 90cm)
1 Ship Case	<b>Weight</b>
	62 lb (28kg)

▼ Imara S6 DMX Kit



**KIT-IM6-1/120**  
Imara S6 DMX Yoke Mount Kit, 120VAC

**KIT-IM6-1/230**  
Imara S6 DMX Yoke Mount Kit, 230VAC

<b>Contents</b>	<b>Dimensions</b>
1 Imara S6 DMX Yoke	31 x 10.5 x 35.5"
1 Jr. Pin	(79 x 27 x 90cm)
1 Ship Case	<b>Weight</b>
	46 lb (21kg)