



KINO FLO[®]
Lighting Systems

SELECT

LED

With Gel presets
& Dial-in 360° Colors



Select LED DMX



Louver



Center Mount



Controller

Select LED has two menus, white and color. The white menu gives the user access to **Dimming, Kelvin** and **Green/Magenta** control channels and Kelvin range is from 2700K tungsten to 6500K daylight.

In the color menu, the Kelvin range travels from 2500K tungsten to 9900K daylight, and Kino Flo has set up a fourth channel called **Gel**. The Gel channel includes Kino Flo presets such as blue & green screen, sodium vapor, mercury vapor and over 100 well known lighting gels. In addition, there is also a fifth channel called **Hue Angle** and sixth channel, **Saturation**. These two channels behave similarly to a traditional color wheel, where you have white light in the center, the Hue angle determines the color along a 360-degree range, and Saturation determines how much color is applied.

The Select LED controller can be mounted to the fixture or run remotely with a 25ft extension cable. We also recently added Snapbag Softbox and Snapgrid accessories.

Features include:

- Tunable Kelvin 2500K to 9900K
- Dimming without color shift
- Green/Magenta control
- Kino Flo presets and Gel presets
- Dial-in color using Hue angle and Saturation control
- Universal input 100-240VAC and 24VDC
- Manual and DMX dimming w/ Auto Terminate
- DMX wireless (Lumen Radio)
- Flicker-free, dead quiet operation

▼ Select LED DMX Systems



CFX-SL30
Select LED 30 Fixture



CFX-SL20
Select LED 20 Fixture



LED-150X-120U
Select LED 150 DMX Controller, Univ 120U

LED-150X-230U
Select LED 150 DMX Controller, Univ 230U

MTP-BC41
Kino 41K Mount w/
Baby Receiver Curve (16mm)



X12-25
Select 150 Extension, 25ft

▼ Photometrics

Select 30	FC	510	161	75	43	28	20	15	11	9	8
	Feet	2	4	6	8	10	12	14	16	18	20
Select 20	FC	508	154	70	40	26	18	14	11	9	7
	Feet	2	4	6	8	10	12	14	16	18	20

Select 30	LUX	7270	2470	1190	683	445	312	233	181	146	117
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5
Select 20	LUX	7113	2409	1121	634	412	288	212	164	131	106
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

▼ LED Fixture Specifications

Fixture	Kelvin Range	Dimming Range	Dimensions	Weight
Select 30	2700-6500 2500-9900	100%-1%	40.5 x 10.5 x 3.5" w/ 6.5" barndoors (103 x 27 x 9cm w/ 16.5cm barndoors)	12 lb (5kg)
Select 20	2700-6500 2500-9900	100%-1%	26.5 x 13 x 3.5" w/ 6" barndoors (67 x 33 x 9cm w/ 15cm barndoors)	10 lb (4.5kg)

▼ LED Controller Specifications

Controller	Input Voltage VAC	Amps VAC	Input Voltage VDC	Amps 24VDC	Kelvin Range	Dimming Range	Dimensions	Weight
LED-150X	100-240VAC, 50/60Hz, 150W	1.3A	18-36VDC, 150W	7.0A	2700-6500 2500-9900	100%-1%	15 x 4.5 x 3" (38 x 11.5 x 8cm)	4.5 lb (2kg)
LED-150X	240-100VAC, 50/60Hz, 150W	0.65A	18-36VDC, 150W	7.0A	2700-6500 2500-9900	100%-1%	15 x 4.5 x 3" (38 x 11.5 x 8cm)	4.5 lb (2kg)

▼ Details



▼ Select LED DMX Systems



SYS-S30-120U

Select LED 30 DMX System, Univ 120U

Contents

- 1 Select LED 30 Fixture
- 1 Select LED 150 DMX Controller
- 1 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)
- 1 Extension, 25ft

SYS-S30-230U

Select LED 30 DMX System, Univ 230U



SYS-S20-120U

Select LED 20 DMX System, Univ 120U

Contents

- 1 Select LED 20 Fixture
- 1 Select LED 150 DMX Controller
- 1 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)
- 1 Extension, 25ft

SYS-S20-230U

Select LED 20 DMX System, Univ 230U

▼ Select LED DMX Accessories/ Cases

	DFS-SL30-H Select 30 Flozier, Half		DFS-SL30-S Select LED 30 Snapbag		MTP-B41F Kino Offset w/ Baby Receiver (16mm)		BAG-SL30 Select LED 30 Soft Case
	DFS-SL20-H Select 20 Flozier, Half		DFS-SL20-S Select LED 20 Snapbag		MTP-BAL Kino Ballast Baby Mount (16mm)		BAG-SL20 Select LED 20 Soft Case
	LVR-SL390-P Select 30 Louver/HP, 90°		LVR-SL340-S Select LED 30 Snapgrid, 40°		STD-M36 Medium Duty, 36"		KAS-DL30 Select LED 30 Flight Case
	LVR-SL360-P Select 30 Louver/HP, 60°		LVR-SL240-S Select LED 20 Snapgrid, 40°		STD-M30 Medium Duty, 30"		KAS-DL20 Select LED 20 Flight Case
	LVR-SL290-P Select 20 Louver/HP, 90°		MTP-KF41 Kino 41K Mount w/ 3/8" Pin (10mm)		STD-D1 Reverse Stand		KAS-SL32 Gaffer LED 30 Ship Case (2-Unit)
	LVR-SL260-P Select 20 Louver/HP, 60°		MTP-BF41S Kino 41K Mount w/ Baby Receiver Short (16mm)		KAS-SL22 Interview LED 20 Ship Case (2-Unit)		KAS-SL33 Select LED 30 Fixture Ship Case (3-Unit)
					KAS-SL23 Select LED 20 Fixture Ship Case (3-Unit)		

Select LED DMX Kits

▼ Select LED 30 DMX Kits



KIT-S30B-120U
Select LED 30 DMX Kit, Univ 120U w/ Soft Case

KIT-S30B-230U
Select LED 30 DMX Kit, Univ 230U w/ Soft Case

Contents	Dimensions	Weight
1 Select LED 30 Fixture	42.5 x 7.5 x 16.5"	26 lb
1 Select LED 150 DMX Controller	(108 x 19 x 42cm)	(12kg)
1 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)		
1 Extension, 25ft		
1 Soft Case		



KIT-S30-120U
Select LED 30 DMX Kit, Univ 120U w/ Flight Case

KIT-S30-230U
Select LED 30 DMX Kit, Univ 230U w/ Flight Case

Contents	Dimensions	Weight
1 Select LED 30 Fixture	46 x 11 x 16.5"	46.5 lb
1 Select LED 150 DMX Controller	(117 x 28 x 42cm)	(21kg)
1 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)		
1 Extension, 25ft		
1 Flight Case		



KIT-S32-120U
Gaffer LED 30 DMX Kit, Univ 120U (2-Unit)

KIT-S32-230U
Gaffer LED 30 DMX Kit, Univ 230U (2-Unit)

Contents	Dimensions	Weight
2 Select LED 30 Fixture	43.5 x 13 x 18.5"	69 lb
2 Select LED 150 DMX Controller	(110.5 x 33 x 47cm)	(31kg)
2 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)		
2 Extension, 25ft		
1 Ship Case		

▼ Select LED 20 DMX Kits



KIT-S20B-120U
Select LED 20 DMX Kit, Univ 120U w/ Soft Case

KIT-S20B-230U
Select LED 20 DMX Kit, Univ 230U w/ Soft Case

Contents	Dimensions	Weight
1 Select LED 20 Fixture	31 x 7.5 x 18"	23 lb
1 Select LED 150 DMX Controller	(79 x 19 x 46cm)	(10.5kg)
1 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)		
1 Extension, 25ft		
1 Soft Case		



KIT-S20-120U
Select LED 20 DMX Kit, Univ 120U w/ Flight Case

KIT-S20-230U
Select LED 20 DMX Kit, Univ 230U w/ Flight Case

Contents	Dimensions	Weight
1 Select LED 20 Fixture	30 x 10.5 x 21"	38 lb
1 Select LED 150 DMX Controller	(76 x 27 x 53cm)	(17kg)
1 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)		
1 Extension, 25ft		
1 Flight Case		



KIT-S22-120U
Interview LED 20 DMX Kit, Univ 120U (2-Unit)

KIT-S22-230U
Interview LED 20 DMX Kit, Univ 230U (2-Unit)

Contents	Dimensions	Weight
2 Select LED 20 Fixture	36 x 13 x 20.5"	63.5 lb
2 Select LED 150 DMX Controller	(91.5 x 33 x 52cm)	(29kg)
2 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)		
2 Extension, 25ft		
1 Ship Case		



Kino Flo Lighting Systems
2840 North Hollywood Way
Burbank, CA 91505

+1 818 767 6528 voice +1 818 767 7517 fax

www.kinoflo.com

© Kino Flo Select LED
No. 3110095 Rev C