

Photometric & Chromaticity Report

Diva Lux 4: Standard Optics-w/Filter lens - 3200K-G/M

Report Summary

Measurements

Fixture Output: 28129 lm

Fixture Peak: 10736 cd

Fixture Efficacy: 67 lm/W

Intensity @ 15m: 48 lux

Color Temperature: 3189 K

CRI: 93.9 CRI R9 Value: 82.0

CQS: 95.0

TLCI: 98

TM-30 Rf: 96.1

TM-30 Rg: 103.2

Beam Angle (50%): 106°

Field Angle (10%): 156°

Cutoff Angle (2%): 168.8°

Conditions

AC Supply: 111 V, 60 Hz

Power: 422.06 W


Current: 3.79 A

Power Factor: 0.99


No photo

This data sheet conforms to American National Standard E1.9 – 2007 (R2017). All data was measured and calculated by a Viso Systems LabSpon Goniometer at the Chauvet PD Optics Laboratory in Davie, FL on 4/7/2025 to LM-63-2002 Standards.

Overall Measurement



Spectral Distribution



Tested Color (CIE 1931):


X: 0.424

Y: 0.399




Light Quality

CRI: 93.9



Color Temperature


3189 K



Photometric & Chromaticity Report

Diva Lux 4: Standard Optics-w/Filter lens - 3200K-G/M

Beam Details




Beam Intensities from 1-20m (3.3-65.6ft)

Distance	1m	2m	3m	4m	5m	6m	7m	8m	9m	10m
Lux	10715	2679	1191	670	429	298	219	167	132	107
Distance	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
Lux	89	74	63	55	48	42	37	33	30	27
Distance	3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft
FC	995	249	111	62	40	28	20	16	12	10
Distance	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
FC	8	7	6	5	4	4	3	3	3	2


Photometric & Chromaticity Report

Diva Lux 4: Standard Optics-w/Filter lens - 3200K-G/M




ISO Diagrams

ISO Candela Diagram




ISO Lux Diagram




Photometric & Chromaticity Report

Diva Lux 4: Standard Optics-w/Filter lens - 3200K-G/M


Chromaticity




CIE 1931 - Zoom



CRI: 93.9 (R1-R8)



CQS: 95.0



Color Parameters

Color Temperature	Color Coordinate CIE 1931	Color Coordinate CIE 1931
CCT	x	y
3189 K	0.424	0.399

Color Deviation from Black Body Curve	Color Coordinate CIE 1964	Color Coordinate CIE 1964
Δuv	y	u
-0.0002	0.399	0.245

Color Rendering Index	Red Component	Color Quality Scale
CRI	CRI - R9	CQS
93.9	82.0	95.0

Television Lighting Consistency Index	Color Fidelity	Color Gamut
TLCI	TM30 - Rf	TM30 Rg
98	96.1	103.2

Photometric & Chromaticity Report

Diva Lux 4: Standard Optics-w/Filter lens - 3200K-G/M

TM-30 Details


Rf 96.1

Fidelity Index
(Rg)

Rg 103.2

Gammut Index (Rg)


Color Vector Graphic




Color Distortion Graphic




		Graphic shifts (%)	
Hue Bin	Rf	Chroma	Hue
1	95	2%	-1%
2	95	2%	-2%
3	95	1%	-2%
4	98	0%	-1%
5	98	0%	1%
6	95	2%	2%
7	95	3%	1%
8	94	3%	-1%
9	96	3%	-1%
10	96	1%	-2%
11	98	1%	-1%
12	96	2%	-2%
13	98	1%	-1%
14	97	2%	1%
15	96	2%	1%
16	95	4%	-2%



Rf by Hue



Local Chroma Shift by Hue



Color Evaluation Sample

